Dell S520 Interactive Projector Instructions for Macintosh

The Dell S520 Interactive Projector is in room 207 Willard Hall Education Building. We recommend that you download the driver and test with your computer before your presentation.

- 1. Press power button on the remote, in the caddy next to the board, one time to turn on projector. Do not press the power button on the projector.
- 2. Plug in the VGA cable attached to the projector to the computer you're using. This may require an adapter, depending on your specific model of computer.
- 3. Make sure your desktop shows on the projector screen; you may need to change your display properties to clone/mirror desktop.
- 4. Plug in the USB cable to an open USB port on your computer.
- 5. Download the Touch Driver from <u>http://www.dell.com/support/home/lc/en/lcdhs1/Drivers/DriversDetails?driverId=DPNV9</u>
- 6. Run and install the downloaded file.
- 7. Once the driver is installed, you should have a green chain link icon in your system bar. Click the icon, then Auto adjust touch for this computer.

🚾 🖫 🕙 🕴 🛜 🜒 🗔 Mon 11:24	4 AM Troubleshooter 🔍 📃
Auto adjust touch for this computer	
Advanced Settings	Calibrate touch
About Dell S520 Touch Driver	Set touch area Set touch sensitivity
Exit	Reset all touch settings an HD
a de la constance de constant	Adjust touch sensor

8. This should take care of adjusting the touch points on the screen. If you place your finger or the stylus on the screen and the cursor is in a different spot, you may need to manually calibrate. For manual calibration on a Macintosh, choose Advanced Settings, Calibrate touch.

- 9. For manual calibration, follow the one screen instructions, if needed. Shadows do seem to cause a disturbance while calibrating, so adjust your position to keep shadows out of the line of site with the calibration dots.
- 10. To power down the projector press the power button on the remote 2 times.
- 11. If you have questions, please contact <u>oet-help@udel.edu</u>.